

# BOLT 83

## Workflow Engineering

# COMPAK

Designed to satisfy the demands of coffee professionals, the **Bolt** offers two functional modes: **Predose** and **Fresh**.

**Instant access** to the grinding chamber for cleaning or burr replacement without losing the adjustment, thanks to the **Lock Load System**.

**Burrs durability: 800 Kg\***. **Long-lasting tempered steel K110** recommended for food use

Motor **630 W**  
Burrs **Ø 83 mm**

### KEY SPECIFICATIONS

Motor output	<b>630</b>	W
Revolutions per minute	<b>1.310</b>	rpm
Ø Burrs	<b>83</b>	mm
Espresso point production*	<b>4,2</b>	g/s
Hopper capacity	<b>1.250</b>	g
Height x width x depth	<b>660 x 230 x 385</b>	mm
Net weight	<b>17,01</b>	kg

\* Production and durability based on a medium roast coffee and grinding point for Espresso. There is a direct relation between the wear of the burrs and the increase in time per dose

### HIGHLIGHTED ELEMENTS



**Predose Mode**  
Selection of 1 or 2 coffees previously ground



**Fresh Mode**  
Selection of 1, 2 or 3 ground doses on demand

### KEY FEATURES

- Micrometric **Parallel System** adjustment
- Instant access** to the grinding chamber (LLS optional)
- Coffee outlet enlightened** with leds
- Motor with fan**
- Adjustable** coffee outlet and fork

### ELECTRONIC FEATURES

- 2.8" TFT touchscreen**
- Multilanguage** display
- Portafilter detector**
- Menu access protection with password**
- Dose counter, both **absolute and relative**
- Wear and changing burrs** alarm
- Screensaver**
- Wifi** optional

